
Edan



Edan SE-1200 Express

- Large high resolution colour • touch screen
- Twelve channel, dual power • supply
- Fully interpretive
- **Preview modes**
- 200 ECG memory

SE-1200 Express	
Acquisition Mode	Simultaneous 12 lead acquisition (Defibrillation protection built-in)
Recording Mode	Auto / Manual / Rhythm
Rhythm Lead	Single lead or three leads selectable
Sensitivity	2.5, 5, 10, 20, 10/5, AGC (mm/mV)
Speed	5mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s (± 3%)
Filter	EMG filter 25Hz/35Hz/45Hz/OFF Automatic Anti Baseline Drift DFT filter 0.05/0.15/0.25/0.5/0.32/0.67Hz Low pass filter 150Hz/100Hz/75Hz AC filter 50Hz/60Hz
Acquisition technology	24 Bits A/D converter - CMRR >115dB
Display	8.4" 800 x 600 dots colour TFT, touch screen
Printer	Thermal printer - Z-fold or roll paper A4
Power Supply	AC: 100V-240V, 50/60Hz
Battery	Built in rechargeable Li-ion battery (approx. printing 300 ECG)
Communication ports	Ethernet, RS232, USB, (WIFI optional)
Safety Standards	IEC 60601-1: 1988+A1+A2, EN 60601-1:1990+A1+A2, IEC/EN60601-2: 2001+A1, IEC/EN60601-2-25, ANSI/AAMI EC-11
Certificate	Australia TGA: ARTG 178086 Class IIa
Dimension	42cmx33cmx12cm
Weight	approximately 5kg (excluding recording paper and battery)



Medical and Surgical Requisites Pty Ltd

Phone 1300 medsurg (1300 633 787)

Call within Brisbane 07 3859 2900 33 Fulcrum Street Richlands Queensland 4077 www.medsurg.com.au Email medical@medsurg.com.au

