

SMOKE SHARK™ II

Bovie®

SMOKE EVACUATION FOR THE OFFICE AND SURGERY CENTER



SMOKE EVACUATOR

PROCEDURE SAFETY

AORN recommends the use of smoke evacuation systems during any medical procedure producing surgical smoke.

REDUCED RISK

500,000 healthcare professionals are exposed to surgical smoke proven to carry viruses, CO, and other chemical and biological hazards. The Smoke Shark II minimizes exposure to these toxic smoke plumes during electrosurgery, laser, and harmonic scalpel procedures.

COST EFFECTIVE

The Extended-Life Filter (SF35) offers up to 35 hours performance reducing procedure cost by 38%(+/-) when used at the lowest setting.

INCREASED EFFICIENCY

The Smoke Shark II Smoke Evacuator is compatible with most electrosurgical generators. The unit operates in conjunction with the optional Bovie Remote Activation Switch (SERS2) for maximized filter life and surgical efficiency.

MODERN DESIGN

A light-weight, ultra-quiet and compact design allowing for simplified operation, storage, and portability.

RELIABLE

The Smoke Shark II Smoke Evacuator includes a standard two (2) year manufacturer warranty.



Established 1922

Medical and Surgical Requisites Pty Ltd

Call within Brisbane 07 3859 2900
Phone 1300medsurg (1300 633 787)

33 Fulcrum Street Richlands Queensland 4077
Email medical@medsurg.com.au

www.medsurg.com.au
Fax 07 3859 2995

STANDARD SETUP



Long-Life 35-hr Filter	Pneumatic Footswitch	Smoke Evacuator Pencil Adapter with 6' Tube*	Remote Switch Activator*
			
SF35 (included)	FSSEP (included)	SEPAT	SERS2

* sold separately

Customize your Smoke Shark™ for a variety of applications by choosing from the accessories below:

6' Tube (non-sterile)	6' Tube with Wand & Tip (non-sterile)	6'Tubing for ValleyLab® & IEC Pencil (sterile)	Laser-Resistant Wand (non-sterile)	Reducer Fitting
				
786T [†]	SETW [†]	SEVL	SELW	SERF [†]

[†] Also available packed sterile

Disposable Suction Coagulators	
Handswitch Activated	Footswitch Activated
	
SCH08 [‡]	SCF08 [‡]

[‡] Other sizes available



OTHER OPTIONAL ACCESSORIES

TECHNICAL SPECIFICATIONS

Smoke Shark II Technical Specifications...

Dimensions:	Line Voltage:	Line Frequency:	Noise Level, dBA:
Height 15.2 cm (6 in.) Width 27.9 cm (11 in.) Depth 39.4 cm (15.5 in.) Weight 4.3 kgs (10 lbs)	SE02: 100/120 VAC SE02-220: 240 VAC	50 - 60 Hz	55.0 dBA (Maximum)
Warranty: limited two (2) year on unit only			

The Smoke Shark II meets U.S. and International Standards.

Rev.8



Medical and Surgical Requisites Pty Ltd

Call within Brisbane 07 3859 2900 33 Fulcrum Street Richlands Queensland 4077 www.medsurg.com.au
Phone 1300medsur (1300 633 787) Email medical@medsur.com.au Fax 07 3859 2995